

eni Rotra Gear EP Tec 85W-140

eni Rotra Gear EP Tec 85W-140 series is an **EP** (Extreme Pressure) gear oil recommended for hypoid gears operating under severe conditions and for very highly loaded gears in general, especially those subject to dynamic loads.

It can also be used in conventional gear-boxes and steering-boxes on cars and trucks, and in gear-boxes, final drives and power take-offs on farm and earth-moving machinery.

It can thus be used for lubricating all gears, whatever they are made of, for which the manufacturer recommend an EP lubricant.

CHARACTERISTICS (typical figures)

SAE Grade		85W-140
Viscosity at 100°C	mm²/s	29.1
Viscosity at 40°C	mm²/s	407
Viscosity Index	-	99
Flash Point COC	°C	240
Pour Point	°C	-18
Mass Density at 15°C	kg/l	0.908

PROPERTIES AND PERFORMANCE

- Its superior EP additives ensure a continuous lubricant film even on gears operating under the severest conditions involving heavy dynamic and shock loads, and very high, or intermittent sliding speeds between the teeth.
- Its outstanding antiwear properties and its oiliness, markedly reduce gear-tooth and bearing wear.
- Its particularly good oxidation stability prevents any deterioration even when in contact with components operating at high temperatures. Thus any tendency for viscosity to increase or for sludge to form is inhibited.
- eni Rotra Gear EP Tec 85W-140 can therefore be kept in use for the long oilservice periods specified by car manufacturers.
- **eni Rotra Gear EP Tec 85W-140** is noncorrosive to steel, copper and other metals and alloys, and thus helps keep lubricated parts in first-class condition.
- Its antirust properties effectively prevent rust on gears and in bearings even when moisture is present.
- Its antifoam qualities minimize the formation of air bubbles which could adversely affect lubricant film continuity.

SPECIFICATIONS

eni Rotra Gear EP Tec 85W-140 is officially approved by or meets the requirements of the following service and specifications:



eni Rotra Gear EP Tec 85W-140

• **API** GL-5