



APPLICATIONS

Eni i-Ride racing tec 5W-40 is an engine lubricant that collects the experience and knowledge acquired in the lubricants sector from Eni research in many decades. It is a synthetic technology lubricant formulated with PAO, which ensures hardware protection and durability essential for motorcycle engines.

CUSTOMER ADVANTAGES

- The raw materials that make up the formulation have been selected to give the product a greater resistance to oxidation phenomena, with consequent stability of its characteristics.
- The viscosimetric characteristics of the product allow obtaining a suitable lubrication of the mechanical components even at high temperatures.
- **Eni i-Ride racing tec 5W-40**, formulated with advanced additive technology, offers appropriate protection against wear phenomena.

SPECIFICATIONS

- JASO MA, MA2
- API SN





CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m ³	852
Viscosity at 100°C	ASTM D 445	mm ² /s	13.8
Viscosity at 40°C	ASTM D 445	mm ² /s	85
Viscosity Index	ASTM D 2270	-	167
Viscosity at -30°C	ASTM D 5293	mPa·s	6300
Flash point COC	ASTM D 92	°C	238
Pour point	ASTM D 5950	°C	-36

