

Eni i-Sint professional MS 5W-30



APPLICATIONS

Mid SAPS synthetic technology engine lubricant developed for modern passenger cars and light duty commercial vehicles equipped with gas exhaust after-treatment systems.

CUSTOMER ADVANTAGES

- Its advanced formulation, meeting ACEA C2 and C3 specifications, helps to increase engine efficiency and improve fuel economy resulting in reduced carbon dioxide (CO₂) emissions.
- **Eni i-Sint professional MS 5W-30** ensures outstanding engine cleanliness, wear protection and strong durability also in the most extreme driving conditions.
- Its enhanced formulation helps prevent or reduce the abnormal fuel combustion event called Low Speed Pre-Ignition (LSPI) that can cause loud knocking noises and, in the most serious case, considerable engine damage (e.g. broken pistons, piston rings, connecting rods and spark plugs).

SPECIFICATIONS

- ACEA C2, C3
- API SN
- MB 229.51



Eni i-Sint professional MS 5W-30



CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m ³	852
Viscosity at 100°C	ASTM D 445	mm ² /s	12.1
Viscosity Index	ASTM D 2270	-	170
Viscosity at -30°C	ASTM D 5293	mPa·s	5500
Flash point COC	ASTM D 92	°C	220
Pour point	ASTM D 5950	°C	-39
B. N.	ASTM D2896	mg KOH/g	8.0

