



## APPLICATIONS

**Eni Arnica 104/FR** is a biodegradable and fire resistant hydraulic oil. It is specifically designed for use in hydraulic systems exposed to fire hazard owing to the presence of ignition sources, such as in metal processing industry.

It is based on propylene glycol and water with good protection against corrosion.

**Eni Arnica 104/FR** may be considered product 'not harmful'. Exhausted product can be wasted as special product.

## CUSTOMER ADVANTAGES

- Inhibits the fire possibility thanks to excellent fire resistance
- Exhausted product can be wasted as special product thanks to base oil type
- Non-corrosive behaviour against metals (steel, cast iron, copper, anodized aluminium, iron)
- Increases system reliability thanks to good antifoam properties

## SPECIFICATIONS & APPROVALS

- VII Report of Luxemburg
- Danieli Standard n. 0.000.001 - Rev.15
- ISO 12922 HFC
- ISO 15380 HEPG





## CHARACTERISTICS

Properties	Method	Unit of Measure	Typical
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	1050
Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	43.0
Water content	ASTM D 95	% (m/m)	45.0

## WARNINGS

- The use of **Eni Arnica 104/FR** depends on compatibility with circuit components, especially seals, flexible piping and paintwork.
- **Eni Arnica 104/FR** should not be used at temperatures above +50°C to reduce water evaporation.

