



## APPLICATIONS

**Eni Dicrea SX 68** is a synthetic lubricant based on polyalphaolefin for rotary and reciprocating air compressors that allows to considerably prolong the oil charge life if compared with mineral lubricants.

## CUSTOMER ADVANTAGES

- Very extended oil draining intervals
- Protection of lubricated components due to an effective antiwear action
- Prevention of deposits and sludge formation resulting in improved operative conditions thanks to an effective thermo-oxidative stability
- Non-corrosive behaviour against metals for an effective antirust action
- Compatibility with rubbers commonly used for seals

## SPECIFICATIONS & APPROVALS

- ISO L-DAB
- ISO L-DAJ
- ABB Turbo HZTL 90617
- DIN 51506 VDL
- Wartsila 4V92A670 Rev. J





## CHARACTERISTICS

Properties	Method	Unit of Measure	Typical
Appearance	APM 27	-	clear
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	840
Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	68
Viscosity index	ASTM D 2270	-	138
Flash point (COC)	ASTM D 92	°C	245
Pour point	ASTM D 97	°C	-51
Rust test/B	ASTM D 665	-	pass
Demulsibility at 54°C	ASTM D 1401	mins	10
Foaming (sequence I)	ASTM D 892	cc/cc	0/0

