

Eni Rotra Truck Gear 85W-140



APPLICATIONS

Eni Rotra Truck Gear 85W-140 is a special API GL-4 and GL-5 E.P. (Extreme Pressure) lubricant for manual and differential gearing hypoid transmissions, operating under particularly severe conditions and subjected to dynamic loads and high operating temperatures. Its particular formulation allows it to be used in all applications for which manufacturers prescribe both GL-4 and GL-5 API level lubricants.

CUSTOMER ADVANTAGES

- It provides excellent resistance to oxidation and protection of metallic surfaces, enabling to cover the long distances required by car manufacturers. It is also perfectly compatible with both gaskets and metals that are part of the manual gearbox synchronizers.

SPECIFICATIONS

- API GL-4, GL-5, MT-1
- SAE J2360
- Scania STO 1 : 0
- ZF TE-ML 2B, 5A, 7A, 12E, 16D, 21A quality



Eni Rotra Truck Gear 85W-140



CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m ³	910
Viscosity at 100°C	ASTM D 445	mm ² /s	28.2
Viscosity Index	ASTM D 2270	-	140
Viscosity at -12°C	ASTM D 2983	mPa·s	30000
Flash point COC	ASTM D 92	°C	210
Pour point	ASTM D 5950	°C	-30

