



## APPLICATIONS

**Eni Rubus TF 0** is a high performance aluminium complex “food grade” grease formulated with pharmaceutical white oil, with PTFE and antiwear, antirust, antioxidant additives.

**Eni Rubus TF 0** has a wide range of applications in food, pharmaceutical and cosmetic industries, particularly recommended for the lubrication of bearings, joints, gaskets, gears, gearboxes and chains where the grease lubrication is requested and operating in severe conditions like in presence of high temperatures and of water.

Particularly suitable for centralized lubrication systems.

**Eni Rubus TF 0** is formulated exclusively with additives listed in the FDA Group 21 CFR 178.3570 and it is free of genetically modified materials, main allergens substances like nut oil, soya oil, dairy industry derivatives and animal derived materials.

## CUSTOMER ADVANTAGES

- Meets the requirements of the HACCP (Hazard Analysis and Critical Control Point) System thanks to NSF H1 (incidental contact with food) registration;
- Suitable for applications at very high and very low temperature thanks to its high thermal stability;
- Very good pumpability at low temperature;
- Good resistance to loads, shocks and vibrations;
- Outstanding resistance to water washout and to the main detergents and cleaners;
- Very good protection of the machinery against rust and corrosion;
- Compatible with the elastomers normally used in food machinery lubrication systems.

## SPECIFICATIONS - APPROVALS

- NSF H1 - n° 151346
- ISO 12924 L-XACDA 0
- DIN 51826 GPF 0K -10
- Kosher





- Halal

## CHARACTERISTICS

Properties	Method	Unit	Typical
Consistency (NLGI grade)	-	-	0
Thickener type	-	-	aluminium complex
Base oil type	-	-	pharmaceutical white oil
Base Oil Viscosity at 40°C	-	-	180
Solid lubricant	-	-	PTFE
Appearance	-	-	smooth
Colour	-	-	white
Dropping point	ASTM D 566	°C	210
Penetration at 60 double stroke	ASTM D 217	dmm	370
4 Balls wear	ASTM D 4172	mm	< 0.7
4 Balls weld load	ASTM D 2596	kg	200
Temperature range		°C	-15/+120

## WARNINGS

- All "food grade" lubricants should be stored apart from other lubricants, chemical substances and foodstuffs and out of direct sunlight or other heat sources. Store between 0° C and +40°C.



eni