



## APPLICATIONS

**Eni Rubus Universal 0** is a “food grade” high performance grease, formulated with a synthetic base oil (PAO), aluminium complex thickener, with a special combination of antiwear, antirust, antioxidant, EP (Extreme Pressure) additives and with white solids lubricants.

**Eni Rubus Universal 0** has a wide range of applications in the food, pharmaceutical, cosmetic, pet food and food for cattle industries.

Fortified with specific tackifier, it is particularly suitable for the lubrication of centrifuges, cams, tracks, bearings, gearboxes, chains, conveyors, joints, gaskets and slides where the above mentioned NLGI grade is required, and in automatic and centralized lubrication systems.

Particularly recommended for the lubrication of components operating in very severe conditions like: in presence of high loads, shocks and vibrations, in hot environments and in presence of steam, in refrigerators or in cold and wet environments, in presence of water, in washing lines of fruits/vegetables and in bottling plants.

**Eni Rubus Universal 0** is formulated exclusively with additives listed in the FDA Group 21 CFR 178.3570 and it is free of genetically modified materials, main allergens substances like nut oil, soya oil, dairy industry derivatives and animal derived materials.

## CUSTOMER ADVANTAGES

- Meets the requirements of the HACCP (Hazard Analysis and Critical Control Point) System thanks to NSF H1 (incidental contact with food) registration;
- Suitable for applications at very high and very low temperature thanks to its high thermal stability;
- Very good pumpability at low temperature and in lubrication centralized systems;
- High resistance to loads, shocks and vibrations;
- Outstanding resistance to water washout and to the main detergents and cleaners;
- Very good protection of the machinery against rust and corrosion;
- Compatible with the elastomers normally used in food machinery lubrication systems.





## SPECIFICATIONS - APPROVALS

- NSF H1 - n° 151352
- ISO 12924 L-XDCDB 0
- DIN 51826 GPFHC OK -40
- Kosher
- Halal

## CHARACTERISTICS

Properties	Method	Unit	Typical
Consistency (NLGI grade)	-	-	0
Thickener type	-	-	aluminium complex
Base oil type	-	-	synthetic
Base Oil Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	350
Solid lubricant	-	-	white solids
Appearance	-	-	smooth
Colour	-	-	whitish
Dropping point	ASTM D 566	°C	>190
Penetration at 60 double stroke	ASTM D 217	dmm	370
4 Balls weld load	ASTM D 2596	kg	350
Temperature range		°C	-40/+130

## WARNINGS

- All "food grade" lubricants should be stored apart from other lubricants, chemical





substances and foodstuffs and out of direct sunlight or other heat sources. Store between 0° C and +40°C.



eni