

Eni RUSTIA C 10W-20

APPLICATIONS

Eni RUSTIA C 10W-20 is a preservative oil designed for the lubrication and protection of gasoline or Diesel engines. It is formulated from a high quality base stock of high Viscosity Index and low pour point, and with suitable additives which ensure very good detergency as well as high antirust, anticorrosion, dispersant, antioxidant, antiwear and antifoam properties.

Eni RUSTIA C 10W-20 should be used in gasoline and Diesel engines when:

- An engine oil is required for vehicles which may be standing unused for long periods without any other protective measure
- An oil is required for initial fill and running-in of new or overhauled engines.

In both cases the oil may be kept in use for the normal service life recommended by the engine manufacturer before draining.

CUSTOMER ADVANTAGES

- **Eni RUSTIA C 10W-20** has very good antirust and anticorrosion properties, which ensure effective engine protection during long periods out of service even in damp climates, saline conditions and presence of acidic products of combustion.
- Its high detergent and dispersant properties reduce formation of lacquer, varnish, sludge and deposits within the motor, keeping rings free and pistons clean and maintaining potential deposit-forming products in suspension.
- It has a good resistance to deterioration by oxidation due to prolonged high-temperature operation in the presence of air and oxidising agents.
- Its antiwear properties ensure long life of working parts and notably reduce the need for engine servicing and overhauls.
- Its antifoam properties prevent the formation of air bubbles which can adversely affect lubricant film continuity.

SPECIFICATIONS

- MIL-L-21260 C



Eni RUSTIA C 10W-20

CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m ³	878
Viscosity at 100°C	ASTM D 445	mm ² /s	7.75
Viscosity at 40°C	ASTM D 445	mm ² /s	48.6
Viscosity Index	ASTM D 2270	-	127
Viscosity at -25°C	ASTM D 5293	mPa·s	6650
Flash point COC	ASTM D 92	°C	230
Pour point	ASTM D 5950	°C	-24

