

Eni i-Sint Super TEC 10W-40



APPLICATIONS

Eni i-Sint Super TEC 10W-40 is a synthetic engine lubricant developed by our researchers based on decades of experience and knowledge.

Its advanced additive technology and carefully selected base oils ensure maximum engine reliability, hardware protection and durability.

CUSTOMER ADVANTAGES

- Excellent anti-wear performance protects components against excessive wear and extends the service life of the engine.
- Outstanding detergency and dispersancy properties minimise the formation of lacquers, sludge and other deposits and prevent piston rings from sticking.
- Good rust and corrosion protection prevents excessive rust and corrosion throughout the service period.
- Superior thermal and oxidative stability reduces oil degradation even when used in the harshest operating conditions and enhances oil longevity.
- Prevents or reduces abnormal fuel combustion events called Low-Speed Pre-Ignition (LSPI).

SPECIFICATIONS

- API SQ
- API CF



Eni i-Sint Super TEC 10W-40



CHARACTERISTICS

Properties	Method	Unit	Typical
Appearance	Visual	-	B&C
Colour	ASTM D 1500	-	L3.5
Density at 15°C	ASTM D 4052	kg/dm ³	0.865
Viscosity at 100°C	ASTM D 445	mm ² /s	14.3
Viscosity at 40°C	ASTM D 445	mm ² /s	96.6
Viscosity Index	ASTM D 2270	-	155
Viscosity at -25°C	ASTM D 5293	mPa·s	5065
Pour point	ASTM D 6749	°C	-45
B. N.	ASTM D 2896	mg KOH/g	6.5

