

# Eni i-Sint super TEC 5W-30



## APPLICATIONS

**Eni i-Sint super TEC 5W-30** is a synthetic engine lubricant developed by our researchers based on decades of experience and knowledge.

Its advanced additive technology and carefully selected base oils ensure maximum engine reliability, fuel economy, hardware protection and durability.

## CUSTOMER ADVANTAGES

- It provides excellent anti-wear performance, protecting components against excessive wear and extending the service life of the engine.
- It has outstanding detergency and dispersancy properties, minimising the formation of lacquers, sludge and other deposits and preventing piston rings from sticking.
- Good rust and corrosion protection prevents excessive rust and corrosion throughout the service period.
- Superior thermal and oxidative stability reduces oil degradation even when used in the harshest operating conditions and enhances oil longevity.
- It prevents or reduces the abnormal fuel combustion event known as Low-Speed Pre-Ignition (LSPI).
- It provides excellent fuel economy, reducing vehicle operating costs.

## SPECIFICATIONS

- API SQ RC
- API CF
- ILSAC GF-7A

# Eni i-Sint super TEC 5W-30



## CHARACTERISTICS

Properties	Method	Unit	Typical
Appearance	-	-	B&C
Colour	ASTM D 1500	-	L3.0
Density at 15°C	ASTM D 4052	kg/dm <sup>3</sup>	0.861
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	10.4
Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	63.3
Viscosity Index	ASTM D 2270	-	153
Viscosity at -30°C	ASTM D 5293	mPa·s	6300
Pour point	ASTM D 6749	°C	-39
B.N.	ASTM D 2896	mg KOH/g	7.7

